



Office de la propriété
intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An Agency of
Industry Canada

*Bureau canadien
des brevets*
Certification

La présente atteste que les documents
ci-joints, dont la liste figure ci-dessous,
sont des copies authentiques des docu-
ments déposés au Bureau des brevets.

*Canadian Patent
Office*
Certification

This is to certify that the documents
attached hereto and identified below are
true copies of the documents on file in
the Patent Office.

Specification and Drawings, as originally filed, with Application for Patent Serial No:
2,394,770, on July 23, 2002, by **BOOMERANG TRACKING INC.**, assignee of André
Eric Boulay and Robert Nelson, for "Vehicle Location System Using a Kinetic Network".


Agent certificateur/Certifying Officer

July 21, 2003

Date

Canada

(CIPO 68)
04-09-02

OPIC  CIPO

VEHICLE LOCATION SYSTEM USING A KINETIC NETWORK**Field of the invention**

5

The present invention relates to a vehicle location system using a kinetic network, and more specifically to a vehicle locator device which can send information to another device when the vehicle locator device cannot or is not adapted to communicate with a wireless network.

10

Description of the prior art

15

Vehicle location systems are becoming well known in the art. One such system is described in US patent no. 5,895,436 (Savoie). In that system, a unit is placed on board a vehicle. When the unit determines that the vehicle has been stolen, or when the owner of the vehicle reports the vehicle as being stolen, a signal is sent to the unit on board the vehicle, and in the solution taught in that patent, a cellular line is opened, which can be tracked by a tracking vehicle. Improvements to this system include a beacon which is located separately or on board the unit and which can be tracked by the tracking vehicle even if the wireless tracking system is jammed, removed, or otherwise not functioning, avoiding the use of costly cellular communications. Other improvements have included two-way communication between the unit on board the vehicle and other sources. This permits, for instance, the unit to verify if an authorized transponder is located adjacent the vehicle. If not, the unit auto-determines that the vehicle has been stolen. Alternatively, a motion sensor can be provided on board the vehicle. Unauthorized movement of the vehicle will trigger the on-board unit to signal a central location that the vehicle has been stolen and is in need of being tracked.

20

25

30

One of the issues that arises with such systems is that wireless network coverage is not universal, and is generally not available in remote locations. Furthermore, some wireless networks cannot communicate in certain

circumstances (deep within underground garages, for example). Thieves are also becoming more sophisticated and are equipped with jammers, which jam wireless signals.

5 Consequently, there can be times when the on-board units "know" the vehicle has been stolen, and are emitting the proper signals, but these signals are not being received by a central location since there is no communication. It is thus almost impossible to locate such vehicles.

Summary of the invention

10

It is an object of the invention to provide an on-board unit with a means for sending and receiving information to and from devices which are not part of a traditional wireless network carrier's infrastructure. Thus, the devices in the vehicles become a mobile wireless network, when one of these devices
15 encounters an activated transmitter, the device sends a signal through the traditional wireless network, revealing the last position of where it saw the activated transmitter. The activated transmitter can emit a signal which is received by a device which in turn can communicate with the central location directly or indirectly, and provide the central location with the identification of the on-board
20 unit, as well as the device's location for generally locating the on-board unit.

Brief description of the drawings

25 The present invention and its advantages will be more easily understood after reading the following non-restrictive description of preferred embodiments thereof, made with reference to the following drawings in which:

Figure 1 is a schematic representation of a stolen vehicle S1, and a plurality of receivers located in the vicinity of S1;

30 Figure 2 is a schematic representation of an on-board unit according to a preferred embodiment of the invention; and

Figure 3 is a schematic representation of the steps for activating a secondary signal of the on-board unit according to a preferred embodiment of the invention.

5 **Description of a preferred embodiment of the invention**

Referring now to Fig. 2, there is shown an on-board unit for locating a stolen vehicle according to a preferred embodiment of the invention. As the on-board unit is known in the art, only its features useful for the present invention will be
10 discussed herein.

On board unit 10 includes a primary communication system 11 for communicating with a central location. This system is more particularly described in US patent no. 5.895.436, the contents of which are hereby incorporated by reference, and in international applications nos. PCT/CA01/00130 and
15 PCT/CA01/01334, in the name of the same assignee. The on-board unit 10 is also provided with another communication system 13, which forms part of the present invention. Preferably, on-board unit 10 is also provided with a memory.

The other communication system 13, or secondary system 13, is adapted to send, over a RF band, a message containing an identification of the on-board unit
20 10. Preferably, the message can also contain other status information, such as the fact that the on-board unit 10 is located on a vehicle that has been stolen, and advantageously information about the status of the vehicle if the on-board unit 10 is in communication with other systems present on the vehicle. For example, the on-board unit could be interfaced with the vehicle's computer, with a microphone
25 located inside the vehicle, with a camera located inside the vehicle, etc.

This secondary system 13 is activated when the on-board unit 10 has failed to communicate with a central location. The system of the present invention is thus particularly adapted to be used with a vehicle location device which "knows" whether or not the vehicle has been stolen.

30 When the on-board unit has failed to communicate with the central location, there is a presumption that the vehicle including the unit 10 is either out-of-range

of the wireless network, or has had its transmitter disabled or torn out. In an alternative embodiment of the invention, the on-board unit 10 is not a vehicle location unit, but is rather an independent unit. This unit can emit the signal as it is adapted to recognize that the vehicle in which it is housed has been stolen, for example, by being in communication with the vehicle location unit.

The emitted signal by the activated transmitter is received by a device which can communicate with the central location. This device or receiver, denoted R on Fig. 1, can be a wireless telephone, a personal digital assistant with wireless communication means, a dedicated device or a vehicle location unit, such as a unit sold under the trade-mark BOOMERANG®. When the receiver is proximate the on-board unit 10, it receives the ID of the on-board unit 10. For example, in Fig. 2, R2 is located proximate S1 and receives the ID of the on-board unit 10. If R2 can communicate with the central location, it relays to the central location its own ID, its location and the ID of S1. Consequently, the central location can take the appropriate measures to attempt to locate the stolen vehicle S1. If however R2 cannot communicate with the central location, i.e. it is out of range itself, or it is being jammed, it stores in its internal memory the ID of S1, and will send it to the central location as soon as communication with the central location can be established. Advantageously, if the receiver R2 is provided with geo-positioning means, it can also store the coordinates and time at which the signal emanating from S1 were received, to facilitate the work of the tracking vehicle.

In an advantageous embodiment of the invention, each vehicle in a fleet of vehicles, for example a fleet of delivery vehicles, could be equipped with receivers. Since these vehicles are constantly in motion in a relatively large geographic area, the plurality of receivers acts as a "kinetic network".

Although the present invention has been explained hereinabove by way of a preferred embodiment thereof, it should be pointed out that any modifications to this preferred embodiment within the scope of the appended claims is not deemed to alter or change the nature and scope of the present invention.